

### Type Lab HSD/Mixer

**HSD Series (High Speed Dissolvers)** 

- HSD EX (Explosion Proof Motor)
- HSD S: (Standard, Non Explosion Motor)
- MX EX : (Explosion Proof Motor)
- MX S : (Standard, Non Explosion Motor)



# PT. PLATINDO CIPTA RAYA **MIXER SPECIALIST**

- PHARMACY INDUSTRY
- **FOOD INDUSTRY**
- INK, PAINT, CHEMICAL INDUSTRY

HSD Lab Dissolver is a high speed dissolver and MX Lab Mixer are designed for laboratory, small production machine and pilot plant application. The construction is very steady, operates smooth and quite.

The speed can be adjusted according to the scale on the control box. It is very convenience to adjust vertically the position of the dispersing blade (on the shaft) by mean of cranking the adjusting hand handle. The unit is equipped with a simple but stable container clamping device.

MX: MIXERS, Use standard 4 pole motor (1450 RPM)

USE ONLY PLATINDO STAINLESS STEEL CONTAINERS FOR OPTIMUM RESULT IN YOUR APPLICATION, WE WILL SELECT THE RIGHT SIZE FOR YOU

## **TECHNICAL SPECIFICATION**

MODEL	POWER (HP)	SPEED (RPM)	DISC DIAMETER ( mm )	LIFTING HIGHT (mm)	CONTAINER VOLUME (L)	WEIGHT ( Kg )	Peripheral Speed ( m/s ) (STANDARD)	REMARK
LAB-HSD-1/3	1/3	3000	30-40	0,4 L	0,6	64,5	0,47	Ready Stock
LAB-HSD-1/2	1/2	3000	40-50	1	1,5	65,5	0,62	Ready Stock
LAB-HSD-1	1.0	3000	50-60	1,75	2,5	70	0,78	Ready Stock
LAB-HSD-2	2.0	3000	60-80	3	5	77,2	0,94	Ready Stock
LAB-MX-1/3	1/3	1500	30	0,6	1	64,5	0,23	Ready Stock
LAB-MX-1/2	1/2	1500	40	1,4	2	65,5	0,31	Ready Stock
LAB-MX-1	1.0	1500	50	2,6	4	70	0,39	Ready Stock
LAB-MX-2	2.0	1500	60	4,5	7	77,2	0,47	Ready Stock

All stipulated data are for reference only, changes may be made without prior notice, for detail information, please contact our office.

By Changing the speed and the HSD Disc to an impeller, The HSD is converted to a Mixer

**HSD**: HIGH SPEED DISSOLVER

Optional: \* EXPLOSION PROOF MOTOR \* FREQUENCY INVERTER FOR VARIABLE SPEED UP TO 6000 RPM

		anne I ar anno anno anno anno anno			
Dimension For All Model	Α	В	C	L	W 545
in mm	250	850	1290	650	
MODEL	DA	DT	HD	HV	НТ
LAB-HSD-1/3	30	90	15	60	100
LAB-HSD-1/2	40	120	20	80	125
LAB-HSD-1	50	150	25	100	150
LAB-HSD-2	60	180	30	120	200
LAB-MX-1/3	30	90	10	90	150
LAB-MX-1/2	40	120	13	120	180
LAB-MX-1	50	150	16	150	225
LAB-MX-2	60	180	20	180	275

